


GNA Series

8 – 16GHz Low Noise Amplifier

Features

- Frequency Range: 8-16GHz
- Gain: 20dB
- P_{1dB}: +13dBm
- IP3: +25dBm
- Noise Figure: 1.9dB (typ.)
- DC Power: +5V to +15V @ 65mA
- Internally Voltage Regulated
- Field Replaceable SMA-F

Photo



Description

GNA-120F is a high performance Microwave Low Noise Amplifier, with standard frequency range of 8GHz to 16GHz.







Electrical Specifications @+25°C, Z_{in}=Z_{out}=50 Ω, V_{supply} = +5VDC

Parameter	Unit	Minimum	Typical	Maximum
Frequency Range	GHz	8		16
Gain (S ₂₁) f = 8GHz	dB		20.5	
f = 12GHz	dB		22.0	
f = 16GHz	dB		21.5	
Gain Variation Over Temperature	dB/°C		0.015	0.025
Output Power P _{1dB}	dBm	+11.5	+13	
Saturated Output Power P _{Sat}	dBm		+15	
Output Third Order Intercept IP3	dBm		+25	
Noise Figure @12GHz	dB		1.9	2.2
Reverse Isolation (S ₁₂) @12GHz	dB		-47	
VSWR-Input (S ₁₁)	ratio:1	2.3 @8GHz	1.4 @12GHz	2.1 @16GHz
VSWR-Output (S ₂₂)	(unitless)	1.6 @8GHz	1.1 @12GHz	1.8 @16GHz
DC Power Supply - voltage	V	5		15
DC Power Supply - current	mA		65	85
Operating Temperature	°C	-40		+85
Size (RF/DC feedthru's excluded)	Inch	1.00 (L) x 0.75 (W) x 0.45 (H)		
Weight	Oz	0.6 (17 grams)		

GNA Series

8 – 16GHz Low Noise Amplifier

Typical Performance @+25 °C



GNA Series

8 – 16GHz Low Noise Amplifier

Absolute Maximum Ratings

Parameter	Absolute Maximum
RF Input Power	+5dBm
Supply Voltage (Survival)	+16V
Operating Temperature	-40 °C to +85 °C
Storage Temperature	-55 °C to +125 °C

Outline

