


## Level 15

## 7-34GHz Frequency Mixer

### Features

- LO/RF: 7–34GHz
- IF: DC–8GHz
- LO Level: +15dBm
- Conversion Loss: 12dB typ.
- RF Input: Up to +13dBm
- Input IP3: +22dBm
- K-2.92mm Female RF/LO Ports
- SMA Female IF Port

### Picture



### Description

GXR-6 is a passive double balanced mixer with 7 to 34GHz at RF/LO port and DC to 8GHz at IF port.







### Electrical Specifications @ +25 °C, IF=500MHz, LO=+15dBm, 50 Ω

Parameter		Unit	Minimum	Typical	Maximum
Frequency Range	LO/RF	GHz	7		34
	IF	GHz	DC		8
LO Power Level		dBm	+13	+15	+17
Conversion Loss	LO/RF: 7-20GHz	dB		11	14
	LO/RF: 20-34GHz	dB		12	15
LO-RF Isolation	LO/RF: 7-20GHz	dB		35	
	LO/RF: 20-34GHz	dB		35	
LO-IF Isolation	LO/RF: 7-20GHz	dB	20	30	
	LO/RF: 20-34GHz	dB	25	40	
RF-IF Isolation	LO/RF: 7-20GHz	dB	7	10	
	LO/RF: 20-34GHz	dB	13	20	
RF Input P <sub>1dB</sub>	LO/RF: 7-20GHz	dBm		+12	
	LO/RF: 20-34GHz	dBm		+13	
Input IP3	LO/RF: 7-20GHz	dBm		+20	
	LO/RF: 20-34GHz	dBm		+22	

## Level 15

## 7-34GHz Frequency Mixer





### Typical Performance



## Level 15

## 7-34GHz Frequency Mixer

### Typical Performance




**Level 15**

**7-34GHz Frequency Mixer**

**Absolute Maximum Ratings**

Parameter	Absolute Maximum
RF Power	+21dBm
LO Driver	+27dBm
Operating Temperature	-40 °C to +85 °C
Storage Temperature	-65 °C to +150 °C

**Schematic**



**Outline**

