

LNA Series

10 – 1500MHz Low Noise Amplifier

Features

- Frequency Range: 10-1500MHz
- Gain: 26dB
- P_{1dB}: +10dBm
- IP3: +23dBm
- Noise Figure: 3.3dB
- DC Power: 12V
- SMA Connector

Picture



Performance measured @ 1500MHz







Description

LNA-1500 is a wideband Low Noise Amplifier operates with frequency range usable from 10 to 1500MHz.

Electrical Specifications @ +25 °C

Parameter	Unit	Minimum	Typical	Maximum
Frequency Range	MHz	10		1500
Gain	f = 40MHz		28	
	f = 500MHz		28	
	f = 1500MHz		26	
P _{1dB}	f = 40MHz		+12	
	f = 500MHz		+12	
	f = 1500MHz		+10	
IP3	f= 1500MHz		+23	
Noise Figure	f = 10MHz		2.9	
	f = 500MHz		3.3	
	f = 1500MHz		3.3	
VSWR	f = 1500MHz			
	Input VSWR		1.5:1	
	Output VSWR		2.0:1	
DC Power Supply	V	9	12	15
Supply Current	mA		45	


Typical Performance @ +25 °C



Absolute Maximum Ratings

Parameter	Absolute Maximum
RF Input Power	+13dBm
Supply Voltage	+16V
Operating Temperature	-40 °C to +85 °C
Storage Temperature	-55 °C to +125 °C

Outline



	A	B	C	D	E	F	G	H	I	J
Inch	1.250	1.250	0.563	0.450	1.000	0.625	1.000	0.250	0.500	0.187
mm	31.75	31.75	14.29	11.43	25.40	15.88	25.40	6.35	12.70	4.76